

Serial No.: Unassigned **Inventor: BATEMAN, Paul** Attorney Docket No.: 49447-2USPX

Express Mail No.: EL258050275US



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of: BATEMAN, Paul

Entitled:

SEPARATION AND DETECTION OF SPERMATOZOA

Box Patent Application Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

EL258050275US

CERTIFICATE OF MAILING BY EXPRESS MAIL
--

"EXPRESS MAIL" Mailing Label No.: EL258050275US Scot. . 8, 2409 Date of Deposit

I hereby certify that this paper, including the documents referred to therein, or fee is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231

Type or Print Name	KOPHU	LANDMAN
·· <u></u>		
Signature	folyon thank	~~~

REQUEST FOR FILING A CONTINUATION OF AN INTERNATIONAL APPLICATION 35 U.S.C. §§ 111(a) and 365(c)

This is a request for filing a continuation application under 37 C.F.R. § 1.53(b) of pending prior International Application Number PCT/GB99/02685, filed on August 13, 1999, entitled SEPARATION AND DETECTION OF SPERMZTOZOA, which designates the United States, hereby incorporated herein by reference, which claims the benefit of British Patent Application No. 9817795.9 filed on August 14, 1998, by the following named inventor(s):

Full Name of Inventor	Family Name BATEMAN	First Given Name Paul	Second Given Name
Residence & Citizenship	City KINGSTON-UPON-THAMES	State or Foreign Country GREAT BRITAIN	Country of Citizenship GREAT BRITAIN
Post Office Address	Post Office Address 12-50 KINGSGATE ROAD, KINGSTON- UPON-THAMES KT2 5AA, GREAT BRITAIN	City KINGSTON-UPON-THAMES	State & Zip Code/Country GREAT BRITAIN

1. ☑ Enclosed are 12 pages of the specification, 5 pages of claims, and 1 page containing the abstract of International Application No. PCT/GB99/02685 as published.

2. \boxtimes The filing fee is calculated on the basis of the claims.

FOR	NUMBER FI	ILED	NUMBER	EXTRA	RA'	ГЕ	CALCULATIONS
TOTAL Claims	30	-20=	10		x \$ 18.	00 =	\$180
INDEPENDENT Claims	2	-3=			x \$ 78.	00 =	0
MULTIPLE DEPEND	MULTIPLE DEPENDENT CLAIM(S) (if applicable) 1 x \$ 130 =						
BASIC FEE							+ \$ 690.00
TOTAL OF ABOVE CALCULATIONS =						\$1,000	
REDUCTION BY ½ FOR FILING BY SMALL ENTITY (Note 37 C.F.R. 1.9, 1.27, 1.28). IF APPLICABLE, VERIFIED STATEMENT MUST BE ATTACHED.						\$	
						Total =	\$1,000

- 3. ☑ The Commissioner is hereby authorized to charge fees under 37 C.F.R. §1.16 and §1.17 which may be required, or credit any overpayment to Deposit Account No. 10-0447, reference 49447-2USPX. A duplicate copy of this sheet is enclosed.
- 4.

 ☐ A check in the amount of \$1,000 for the application fee is enclosed.
- 5. ☑ **UNEXECUTED** Declaration with Power of Attorney from the inventor(s).
- 6. □ Certified copy of Priority Document
- 7. □ Applicant is a small entity. A Statement to establish small entity status under 37 C.F.R. 1.9 and 1.27 is enclosed.
- 8. ☑ Priority of foreign application number 9817795.9 filed on August 14, 1998 in Great Britain is claimed under 35 U.S.C. § 119(a)-(d).
- 9.

 Amend the specification by inserting before TECHNICAL FIELD on the first line the sentence: "This application is a continuation of International Application No. PCT/GB99/02685, filed on August 13, 1999, pending, which claims the benefit of British Patent Application No. 9817795.9 filed on August 14, 1998."
- 10. Two sheets of formal drawings are enclosed.
- 11.⊠ A Preliminary Amendment is enclosed.

12. ■ Address all future communications to:

P. Weston Musselman, Jr. JENKENS & GILCHRIST, P.C. 1445 Ross Avenue, Suite 3200 Dallas, Texas 75202-2799

- 13.

 ☐ A Petition to Make Special For New Application Under MPEP § 708.02, VIII is enclosed, along with PTO Form A820 (formerly PTO-1449), and a copy of each prior art reference identified on PTO Form A820.
- Also enclosed: 14. ⊠
 - Certificate of Express Mailing No. EL258050275US 1.
 - 2. Postcard

Respectfully submitted, JENKENS & GILCHRIST, P.C.

P. Weston Musselman, Jr.

Reg. No. 31,644

Date: SEPTEMBER 8, 2000

Jenkens & Gilchrist, P.C. 1445 Ross Avenue, Suite 3200 Dallas, Texas 75202-2799

Telephone: (214) 855-4764

Facsimile: (214) 855-4300

Serial No.: Unassigned Inventor: BATEMAN, Paul Attorney Docket No.: 49447-2USPX Express Mail No.: EL258050275US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of: BATEMAN, Paul

Entitled: SEPARATION AND DETECTION OF SPERMATOZOA

Box Patent Application Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

"EXPRESS MAIL" Mailing Label No.: EL258050275US
Date of Deposit

I hereby certify that this paper, including the documents referred to therein, or fee is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231

Type or Print Name

PRELIMINARY AMENDMENT

Applicant respectfully requests the Examiner to consider the following amendment and comments.

IN THE SPECIFICATION

Please amend the specification as follows:

Insert on the first line of page one before TECHNICAL FIELD the sentence: "This application is a continuation of International Application No. PCT/GB99/02685, filed on August 13, 1999, pending, which claims the benefit of British Patent Application No. 9817795.9 filed on August 14, 1998."

On Page 3, line 16, page 3, line 19, page 4, line 20, and page 7, line 26, delete "PCT/GB99/01929" and insert therefor --WO99/66331--.

On page 3, line 30, insert -- the same or -- after "recognise".

IN THE CLAIMS

Cancel Claims 5, 11, 32-44 and 46-51.

Claim 1, line 6, delete "substantially."

Claim 6, line 17, delete "any preceding claim" and insert therefor -- Claim 1--.

Claim 9, line 24, delete "any preceding claim" and insert therefor -- Claim 1--.

Claim 10, line 27, insert after " $800\mu m$ " --, more preferably $600\mu m$ --.

Claim 12, line 1, delete "any preceding claim" and insert therefor -- Claim 1--.

Claim 13, line 3, delete "any preceding claim" and insert therefor -- Claim 2--.

Claim 13, line 3, delete "filter" and insert therefor --apparatus--.

Claim 14, line 5, delete "any of claims 6 to 13" and insert therefor -- Claim 6--.

Claim 17, line 14, delete "any of claims 6 to 16" and insert therefor -- Claim 6--.

Claim 19, line 18, delete "any of claims 6 to 18" and insert therefor -- Claim 6--.

Claim 23, line 1, delete "claim 21 or claim 22,."

Claim 24, line 4, delete "claim 21 or claim 22,."

Claim 25, line 7, delete "any of claims 6 to 24" and insert therefor -- Claim 6--.

Claim 28, line 13, delete "claim 26 or claim 27,."

Claim 29, line 15, delete "claim 26 or claim 27,."

Claim 31, line 19, delete "any of the preceding claims" and insert therefor -- Claim 1--.

Claim 45, line 25, after "surface," insert --, wherein the filter is the filter contained within the apparatus of any of claims 1 to 31,--.

REMARKS

Applicant requests that the Examiner amend the specification as noted above. The amendments are being made (1) to include related application data on page one, (2) to replace within the specification PCT application number No. PCT/GB99/01929 with the PCT publication number WO99/66331, and (3) to include on page 3, line 60 a statement corresponding to Claim 24 as filed. No new matter has been included. It is believed that no supplemental fees are required for entry of this Preliminary Amendment. However, the Commissioner is hereby authorized to charge any amount required or credit any overpayment in connection therewith to deposit account number 10-0447 of Jenkens & Gilchrist, P.C.

To reduce the number of claims, the "kit" claims 32-44, the method claims 46-47, as well as Claims 48-51, have been deleted. The features of Claim 46 have been introduced into Claim 45.

Respectfully submitted,

JENKENS & GILCHRIST, P.C.

P. Westen Musselman, Jr.

Reg. No. 31,644

Date: SEPTEMBER 8, 2000

Jenkens & Gilchrist, P.C. 1445 Ross Avenue, Suite 3200 Dallas, Texas 75202-2799

Telephone: (214) 855-4764 Facsimile: (214) 855-4300

SEPARATION AND DETECTION OF SPERMATOZOA

TECHNICAL FIELD

This invention relates to the separation and detection of spermatozoa. It provides methods and kits for the separation and/or detection of motile spermatozoa in a sample, which are useful in a number of applications, including the diagnosis and treatment of male infertility.

BACKGROUND ART

5

10

15

20

25

30

It has been estimated that approximately 14-16% of all couples attempting to conceive experience difficulty, and are defined by fertility therapists as infertile. 40% of these cases result from male factors. In a substantial proportion of these, treatment is available to ameliorate or relieve the condition which leads to infertility.

Other conditions also exist in which it is desirable to test for the presence or otherwise of viable spermatozoa in a sample. For example, vasectomies are now frequently carried out as a method of contraception, but it is necessary to verify the effectiveness of a vasectomy by confirming that ejaculate is free of viable spermatozoa for a period of time after the operation.

A number of methods exist for assessing the motility and number of spermatozoa in a sample. One such method is microscopic analysis, which is typically carried out in a hospital or commercial laboratory. More recently, however, a number of proposals have been made for test kits which are intended to simplify the detection of spermatozoa, and which may therefore be useful in the diagnosis of male infertility. For example, WO97/40386 discloses a kit which is based on the detection of the 34kD human epididymal spermatozoa protein (P34H). This protein is thought to be involved in spermatozoa-zona pellucida interaction. The test kit disclosed in WO97/40386 uses an antibody raised against P34H or a related antigen, and a reagent for detecting antibody binding to P34H. As disclosed in WO97/40386, spermatozoa in a test sample are washed three times by centrifugation in Dulbecco-phosphate buffered saline. The samples are then heat denatured at 95°C, centrifuged at 14000g, and the supernatants are then used for analysis.

EP-A-0387873 also discloses a kit for the evaluation of male fertility. This kit uses solid beads to which is bound an antibody specific to an antigenic site on the human spermatozoon acrosome. Such beads are mixed with a test sample, and incubated for a period of 10 to 30 minutes. The test beads are then separated from the suspension, washed and subjected to

10

20

measurement of the number of spermatozoa bound to the solid beads, preferably by examination with the aid of a microscope.

A kit for the detection of spermatozoa in a sample is also disclosed in WO95/29188. In this case, the test is based on antibodies to an antigen such as the SP-10 antigen of human spermatozoa.

A significant disadvantage of the test kits disclosed in the prior art mentioned above is that they do not distinguish between motile and non-motile spermatozoa. In the detection of male infertility, the ability to assess the numbers of motile spermatozoa is the most predictive indicator of male infertility. Moreover, many of the prior art test kits involve procedures, such as centrifugation or microscopic examination, which do not lend themselves to home use, instead requiring implementation by a skilled practitioner.

It is therefore desired to provide a device, which can be self contained or provided in a plurality of components, and a method for separating motile spermatozoa from non-motile spermatozoa, and for collecting and detecting the presence of the motile spermatozoa.

15 **DISCLOSURE OF INVENTION**

The invention provides an apparatus for separating motile spermatozoa from non-motile spermatozoa in a liquid sample, the apparatus comprising (i) a vessel having a sample receiving inlet, a filtered sample outlet and a sample separation filter mounted therebetween, the sample separation filter having a sample-receiving surface and an opposed surface, and the sample separation filter being effective substantially to prevent flow of the sample therethrough, but permitting passage of motile spermatozoa therethrough when said opposed surface of said sample separation filter is placed in contact with a liquid medium and (ii) means for supplying a liquid to said opposed surface of said filter. The sample may comprise motile spermatozoa, non-motile spermatozoa and/or spermatozoa with reduced motility.

In order to detect the separated motile spermatozoa, spermatozoa detection means such as a spermatozoa detection filter may be provided at a sample outlet side of the sample separation filter, and spaced therefrom. The detection means may be integral with the apparatus, or it may be provided as a separate component thereof for inserting into the apparatus before, during or after placing the filter in contact with the liquid medium. The spermatozoa detection filter may have similar characteristics to the sample separation filter.

15

20

25

30

WO 00/09648 PCT/GB99/02685

The filters may have a thickness of 100-2000µm, preferably 200-1000µm, and more preferably 400-800µm. For example, the filters may have a thickness of about 600µm. The minimum particle retention size of the filters may be 5-100µm, preferably 8-60µm, and more preferably 10-40µm. The filters may be fibrous, for example made of glass wool or polypropylene, or they may have a gel or a foam construction. For gel or foam constructions that are not self supporting, an underlying grid lattice or other support may be provided. A particularly preferred filter is a glass fibre filter, which may include a binder such as an acrylic ester. It will be appreciated that the use of a gel as the filter can avoid the need to supply liquid

to its opposed surface, because the gel itself acts as suitable means for achieving this.

10 Preferred gels are hyaluronic acid and methylcellulose.

A reagent or a combination of reagents may be located in the spermatozoa detection means which are directly or indirectly capable of generating a visual signal on interaction with spermatozoa. These reagent or combination of reagents may include antibodies that detect an antigen present on spermatozoa and/or may be capable of binding spermatozoa. Spermatozoa, when immobilised by such antibodies, could be visually detected using a visually detectable reagent which binds to spermatozoa. Antibodies to CD59, as discussed in PCT/GB99/01929, the complete disclosure of which are incorporated herein by reference, have been found to be suitable for this purpose.

A spermatozoa chemoattractant, such as follicular fluid as identified in PCT/GB99/01929, may be located in the spermatozoa detection means. Such spermatozoa chemoattractants are preferably located in a portion of the spermatozoa detection means distal from the sample separation filter.

A pick-up zone may be located either in the sample separation filter or the spermatozoa detection means, said pick-up zone comprising a reagent or combination of reagents which is/are capable of binding to spermatozoa and being transported therewith through the filter(s) to a detection area of the spermatozoa detection means. The reagent or combination of reagents of the pick-up zone may include antibodies that detect an antigen present on spermatozoa. These antibodies may be detectably labelled, for example with gold particles.

The antibodies that are located in the detection area of the spermatozoa detection means may recognise a different spermatozoa antigen from those located in the pick-up zone.

10

15

20

WO 00/09648 PCT/GB99/02685

-4-

The spermatozoa detection means may comprise a spermatozoa acrosome-lysing reagent and a means for detecting pH change. The spermatozoa acrosome-lysing reagent is typically a lysis buffer, and may comprise Proteinase K or the calcium ionophore A24297. The means for detecting pH change could be a pH sensitive probe or a pH indicator reagent capable of visually detecting a pH change, for example bromocresol purple.

The sample receiving surface of the sample separating filter may contain an enzymatic liquefaction agent, such as chymotrypsin, capable of causing semen liquefaction.

The invention also provides a male fertility testing kit comprising an apparatus as described above, the kit further comprising a liquid release mechanism, wherein upon activation of the liquid release mechanism, liquid from a liquid supply is applied to said opposed surface of the sample separation filter to provide liquid communication with a spermatozoa detection means.

The spermatozoa detection means may be integral with the apparatus or it may be provided as a separate or separable component of the kit.

The kit may comprise an integral liquid supply, or an external liquid supply may be used. It will be appreciated that the liquid must be one in which motile spermatozoa remain motile for a sufficient period of time to migrate to the spermatozoa detection means, *ie.* the liquid is generally non-toxic to spermatozoa. However, the liquid may be such that is has a toxicity to spermatozoa that is sufficiently low that enough spermatozoa will successfully reach the detecting means. The liquid is preferably a buffer such as phosphate buffered saline (PBS) or Earle's Balanced Salt Solution (EBSS), as described in PCT/GB99/01929.

It will be appreciated that, where a gel-based filter is used, the gel can act as its own liquid supply. It may be desirable, however, to supply liquid to the opposed surface of a gel-based filter, for instance to dilute a sample after separation through the filter.

The kit may comprise two or more separable components, for example the apparatus and a base unit for the apparatus to engage with. Application of the apparatus to the base unit may be adapted to activate the liquid release mechanism, thereby wetting the spermatozoa detection filter and sample separation means. Alternatively, a button release for the liquid may be provided. The wetting of the spermatozoa detecting filter may activate the detecting agents applied to the spermatozoa detecting means.

15

20

WO 00/09648 PCT/GB99/02685

-5-

An overflow container for catching excess liquid applied to the apparatus upon activation of the liquid release mechanism may be provided.

The liquid supply may comprise a frangible compartment or portion, wherein the liquid release mechanism breaks the compartment to release liquid contained therein. The liquid thereby released may then be channelled by a ramp towards a well formed between the apparatus and a base portion of the kit. The compartment may be piercable by a liquid release mechanism in the form of a piercing mechanism, for example retained by a stop, the stop preventing the piercing mechanism from piercing the compartment until activated by a user.

The invention also provides a method of detecting the presence of motile sperm in a sample, comprising the steps of providing a filter having first and second surfaces, the filter permitting migration of the motile sperm therethrough when a liquid is applied to the second surface, applying the sample to the first surface, applying a liquid to the second surface, and detecting sperm that has migrated through the filter. The sample may be a mixture comprising motile and non-motile spermatozoa. The filter may be the filter contained within the apparatus or the kit as described above.

BRIEF DESCRIPTION OF DRAWINGS

Figure 1 shows a kit in accordance with the present invention prior to application of a vessel to a base unit. Figure 2 shows the kit of Figure 1, with an overflow, after application of the vessel to the base unit. Figure 3 shows an alternative embodiment in which the detection means is a separable component of the kit.

MODES FOR CARRYING OUT THE INVENTION

A kit 10 for testing male fertility is shown in Figures 1 and 2. The kit comprises a vessel 12, a base unit 14, a liquid supply 16 containing liquid 18, and two filters 20,22.

The first filter 20 is a sample separation filter 20 which forms a hindrance to transmission of spermatozoa due to the composition and construction thereof. For example, the filter will substantially retain on a sample receiving surface thereof seminal fluid and non-motile spermatozoa present in a sample deposited thereon. This may be by virtue of the pore size of the filter, for example. Non-motile spermatozoa will not pass through the filter. However, where the spermatozoa are motile, they will be able to "swim" through the filter.

15

20

25

The head of a human spermatozoon is typically 3-5µm in diameter, and tail length is approximately 50-60µm. The filter should be such that these spermatozoa can swim through the filter upon application of the liquid to the opposed surface. Suitable filter materials may be identified by a series of simple experiments.

5 Experiment 1: The assessment of sperm toxicity.

A swim up from a semen sample is prepared (Practical Laboratory Andrology – David Mortimer, page 272) and the resultant preparation of motile spermatozoa is used for the assessment of sperm toxicity of the filter. A 2cm by 2cm square of the filter is cut into 2mm by 1cm strips. 3x 1ml aliquots of the freshly prepared motile sample are added to round bottom tubes (eg., Falcon no. 2001 or 2037) marked duplicate A, duplicate B and control C. 10 of the thin strips of filter are placed in each of duplicate A and B. A, B and C are then incubated at 37°C for 1 hour with frequent agitation. Sperm motility and/or sperm vitality assessment is then performed (Practical Laboratory Andrology, pages 49-50 for motility and pages 66-69 for vitality) on both duplicates and the control. A marked difference in sperm motility and or vitality between the filter containing sample and the control indicates that the filter is toxic to sperm.

Experiment 2: The evaluation of sperm "wicking" through a filter.

200µl of liquefied semen is placed in a round bottom tube. A 0.5cm by 4cm strip of filter is then introduced to the semen sample, such that only the lower 1-2mm of the filter is in direct contact with the semen sample. In some filters, the semen sample will move by capillary action or "wick" up the filter taking with it motile and non-motile spermatozoa, therein invalidating the separation. The extent of wicking in a given time frame eg. 15 minutes, can be determined by removing the filter from the semen sample and analysing with light microscopy 2mm segments of the filter for the presence of spermatozoa. In order to be an effective separator of motile spermatozoa from a mixture of motile and non-motile sperm, the extent of wicking in the filter (in the time frame that the sample will be left applied to the filter prior to detection or collection of the filtered motile sperm) should be less than the thickness of the filter.

Experiment 3: Efficacy of a filter to prevent the passage of dead or immobile spermatozoa

A sample of dead or immobilised sperm is obtained by either heating a semen sample at 95°C in a water bath or by adding a 10% cyanide solution. 200µl of a dead or immobilised semen

10

15

20

25

30

WO 00/09648 PCT/GB99/02685
-7-

sample is applied to the upper surface of the filter, the underside of the filter being in direct communication with 1 ml of EBSS. After 5, 10, 15 and 30-minute intervals, a 10µl aliquot of the filtrate is removed and examined under light microscopy for the presence of spermatozoa. An effective filter will not allow the passage of dead or immobile spermatozoa for the duration that the semen sample is required to be in contact with the upper surface of the filter.

Experiment 4: Efficacy of a filter to selectively allow the passage of motile spermatozoa.

Andrology, pages 49-50) and the characteristics noted. 250µl of the semen sample is applied to the upper surface of the filter, the underside of the filter being in direct communication with 1 ml of EBSS. After 5, 10, 15 and 30-minute intervals, a 10µl aliquot of the filtrate is removed and examined under light microscopy for the presence of motile spermatozoa and the ratio of motile versus non-motile spermatozoa in the filtrate compared to that of the original sample. An effective filter should allow the passage of motile spermatozoa. For example if the original semen sample had a motility of 40% (*ie.* 60% of spermatozoa are non-motile), the filtrate should preferably have a motility of at least 90% with less than 10% being non-motile.

The second filter 22 of the kit is a spermatozoa detection filter 22. The spermatozoa detection filter 22 forms a detection zone 26 for the spermatozoa that can migrate through the sample separation filter 20. The detection zone 26 is provided within the spermatozoa detection filter 22, and comprises a reagent capable of generating a signal upon interaction with spermatozoa. However, a gap 24 is formed between the two filters 20,22 to prevent activation of the kit until such time that a transport medium, for example the liquid 18 in the liquid supply 16, has been supplied to fill the gap 24 to enable the spermatozoa to be transmitted to the detection zone 26, and thus the fertility test to be conducted with the kit.

The composition and construction of suitable filters 20,22 and the detection zone 26 may be such as that described herein, or such as that described in further detail in the prior art. However, preferable compositions and constructions are as described in PCT/GB99/01929, the complete disclosures of which are incorporated herein by reference. A particularly preferred filter material is identified as Filter 4622, available from Ahlstrom Filtration, Inc., 122 W. Butler Street, PO Box A, Mt. Holly Springs, PA 17065-0238, USA. It comprises a micro glass fibre with an acrylic binder. The acrylic latex is an anionic dispersion of acrylate polymers and

10

15

25

30

WO 00/09648 PCT/GB99/02685

-8-

copolymers in a water base. These polymers are based on acrylic esters. The pore size is $20\mu m$ and the thickness is $580\mu m$.

The vessel 12 has a circular cross section with a side wall 28, an open top 30, an annular base 32 and an open nozzle 34 formed on the annular base 32. The spermatozoa detection filter 22 is provided within the nozzle 34. A cap (not shown) may be placed onto the open top 30 for maintaining a sterile environment within the vessel 12. The cap over the open top 30 would need to be removed for application of a sample into the vessel 12.

The base unit 14 comprises the liquid supply 16, a liquid release mechanism 36 and a well 38. The well 38 comprises a hole 40 adapted to receive the nozzle 34. The hole 40 may have a window (not shown) provided therein for inspection of the detection zone 26 after activation of the kit 10. The base unit 14 further comprises a ramp 42 for channelling liquid 18 from the liquid supply 16 into the well 38, and an overflow 44 for catching excess liquid 18 provided into the well 38 from the liquid supply 16.

The liquid release mechanism 36 is in the form of a piercing member 37 adapted to be activated by application of the vessel 12 onto the base unit 14. Prior to activation of the piercing member 37, the piercing member 37 is retained by a stop 48. Application of the vessel 12 draws the piercing member 37 past the stop 48. A frangible portion may be provided for the liquid supply 16 for puncturing with the piercing member 37 as it draws past the stop 48. This frangible portion may comprise a tin-foil wall section.

20 Experiment 5: Separation of motile spermatozoa using gel filters

Various gel-like filters can be used for the spermatozoa separation. The gel media were obtained from Sigma-Aldrich or Pharmacia-Upjohn and were resuspended in EBSS (Gibco-BRL). Four different hyaluronic acid gels and one methylcellulose gel were tested.

Flattened glass capillary tubes (Camlab), with dimensions 1.2 x 4.8mm and an inner diameter vision path of 0.4mm, were filled with the resuspended media, with one end sealed. The open end of the tube was placed in a 1.5ml microfuge tube containing 100µl or 200µl liquefied semen. Sperm were allowed to migrate into the gel for 30min at room temperature, and the tube was wiped and observed under the microscope.

The numbers of spermatozoa at 1cm distances from the open end of the tube were recorded in order to assess the penetration and migration in the various gels. Numbers of spermatozoa per

field of view, using x10 or x20 objectives and a x10 eyepiece to give final magnification of x100 or x200, were counted on an Olympus BH-2 microscope. The area observed at 100x magnification was 0.785mm²; at 200x magnification, the area was 0.196mm².

The results for the four hyaluronic acid products were as follows:

Gel	Initial number of sperm (x10 ⁶)	Initial sperm	3.6 ·dl	Num	ber of	sperma	tozoa
concentration (mg/ml)		motility (%)	Magnif ^a	1cm	2cm	3em	4cm
Hyaluronic acid	$1 - MW: 3-5.8x10^6$, from human um	bilical cord	!			
1	01	91 69 x20		180	50	30	-
0.5	91	09	AZO	150	38	20	-
Hyaluronic acid	$2 - MW: \sim 2x10^6$, fr	rom rooster comb)				
5	126	79 x		69	12	5	-
2			x20	-	-	-	-
1				300	2	-	-
0.5				150	2	-	-
Hyaluronic acid	3 - MW: 0.85-1.6x	10 ⁶ , from Strepto	coccus zoo	epidemi	cus		
2				40	7	4	-
1	126	79	x20	59	1	-	-
0.5	-			16	2	-	-
Hyaluronic acid	1 – Healonid from	Pharmacia-Upjo	hn				
1.25	05	69	x20	300	180	22	5
0.625	95	09	λ20	280	130	15	5

The results for methylcellulose at a viscosity of 15cp were as follows:

Gel	centration of sperm motility Magnif	_		Number of spermatozoa				
concentration (mg/ml)		1cm	2cm	3cm	4cm			
Semen sample 1	<u> </u>		<u> </u>		1	.l		
10				68	4	-		
0.55				74	4	1	-	
2	22	79	x20	80	8	-	-	
1				50	4	-	-	
0.5	-			23	6	-	-	

Semen sample 2							
20				10	-	-	
10	52		x10	116	20	5	-
5	52	61		115	8	3	-
2.5			x20	82	12	3	-
Semen sample 3							
10	22	90	x10	80	1	-	-
5	33	88	XIO	68	-	_	-
Semen sample 4							
10	91	69	x20	120	6	2	-

The results for methylcellulose at a viscosity of 4000cp were as follows:

Gel	Initial number of sperm (x10 ⁶)	Initial sperm motility (%)	Magnif	Number of spermatozoa			
concentration (mg/ml)				1cm	2cm	3cm	4cm
Semen sample 1			1				
10	160	80	x20	250	62	18	-
5	160	80	X20	150	5		-
Semen sample 2							
10	5	<i>EA</i>	x10	5*	-	-	<u> </u>
5	5	64		1*	-	-	-
Semen sample 3			<u>.</u>				
10	160	0	x10	-	-	-	-
5	160	0		-	-	-	-
Semen sample 4			<u> </u>	<u> </u>			
10		7.5	-10	120	8	-	-
5	- 66	75	x10	80	2	-	-
Semen sample 5							
10	33 -	88	x10	510	8	-	-
Semen sample 6							
10	101	64	x20	250	50	28	12

* - these two measurements taken at 0.25cm from open end

It is evident, therefore, that gels can be used as filters to separate motile sperm from a sample containing spermatozoa.

10

15

20

25

WO 00/09648 PCT/GB99/02685

-11-

A process of performing a male fertility test with the above-described kit will now be described.

A sample of seminal fluid 46, or ejaculate, is deposited within an unused or recycled vessel 12 through the open top 30 and onto the sample separation filter 20. The sample may be deposited, for example, by direct application by the user, or by a pipette application from an ejaculated semen sample, The thereby primed vessel 12 is then applied to an unused or recycled base unit 14 which has a fresh liquid supply 16 such that the nozzle 34 of the vessel 12 is inserted within the hole 40 of the base unit 14. During the application of the vessel 12 to the base unit 14, the side wall 28 of the vessel 12 activates the piercing member 37 to puncture the liquid supply 16, as shown in figure 2, in which the piercing member 37 has pierced through the frangible portion of the liquid supply 16. Alternatively, a piercing button 50, see Figure 3, may be provided for piercing the liquid supply 16.

Upon piercing the liquid supply 16, the liquid 18 contained within the liquid supply 16 is channelled down the ramp 42 into the well 38, filling the hole 40 and the well 38 with liquid 18, the liquid 18 also entering through the nozzle 34 of the vessel 12, which is located within the hole 40 of the base unit 14. Thereby, the liquid passes through the spermatozoa detecting filter 22 to fill the gap 24 between the two filters 20,22 with the liquid 18. Excess liquid 18 overflows the well 38 and is collected by the overflow 44.

The liquid 18 acts as a transport medium for spermatozoa that has migrated through the sample separation filter 20 to permit the spermatozoa to migrate beyond the sample separation filter 20 towards the spermatozoa detecting filter 22, so that it may be detected by the detection zone 26 within the spermatozoa detecting filter 22. Upon detection of spermatozoa at the detection zone 26, a signal is produced by the reagent provided thereat, thus signifying presence of motile spermatozoa. In the absence of motile spermatozoa in the sample, no spermatozoa will reach the detection zone 26 since non-motile or reduced-motile spermatozoa will not pass through the sample separation filter 20.

The kit 10 of Figure 3 is an alternative embodiment of the present invention. It has an open top 30 exposing a sample separation filter 20 as described above. A sample 46 is shown deposited onto the sample separation filter 20 on a sample receiving surface thereof.

The side wall 28 of the kit 10 defines a well 38. A liquid supply 16 is provided integral with the kit 10, adjacent the well 38, the liquid supply 16 containing liquid 18 and having a

15

WO 00/09648 PCT/GB99/02685

-12-

frangible portion 60 on a periphery thereof for separating the liquid supply 18 from the well 38 prior to activation of the kit 10. A spermatozoa detection filter 22 is provided on a slide member 56 which may be slidably attached to the kit 10, or it may be provided as a separate component of the kit insertable through a sealable opening 58 in the side wall 28 for conducting a detection of spermatozoa within the well 38.

The liquid release mechanism comprises a piercing button 50 and a piercing member 37. The piercing button 50 is biased into a non-piercing position by a spring 52. Pressing the piercing button drives the piercing member 37 through the frangible portion 60 of the liquid supply, thus allowing liquid 18 contained in the liquid supply 16 to flow into the well 38.

Alternatively, the slide member 56 could be adapted to release the liquid 18 within the liquid supply 16 automatically upon insertion thereof within the well 38, for example by providing a piercing member thereon which would pierce the frangible portion 60 of the liquid supply 16.

A transparent window 54 is provided in the side wall 28 of the well 38 to enable an inspection of the detecting zone 26 contained within the spermatozoa detecting filter to be performed. However, the side wall 28 may be manufactured of a transparent material, thus avoiding the need for the window 54.

The principle of use for the kit 10 of Figure 3 is similar to that of the embodiments of Figures 1 and 2. However, the liquid 18 may be released into the well prior, during or after insertion of the spermatozoa detecting filter within the well.

It will, of course, be understood that the present invention, and in particular the kit and a method of its use, has been described above purely by way of example. Modifications may be made whilst remaining within the scope and spirit of the invention.

CLAIMS

5

- 1. An apparatus for separating motile spermatozoa from non-motile spermatozoa in a liquid sample, the apparatus comprising (i) a vessel having a sample receiving inlet, a filtered sample outlet and a sample separation filter mounted therebetween, the sample separation filter having a sample-receiving surface and an opposed surface, and the sample separation filter being effective substantially to prevent flow of the sample therethrough, but permitting passage of motile spermatozoa therethrough when said opposed surface of said sample separation filter is placed in contact with a liquid medium and (ii) means for supplying a liquid to said opposed surface of said filter.
- 10 2. An apparatus according to claim 1, wherein the sample separation filter is of a gel or foam construction.
 - 3. An apparatus according to claim 1, wherein the filter is fibrous.
 - 4. An apparatus according to claim 3, wherein the fibrous filter is made of glass wool or polypropylene.
- 15 5. An apparatus according to any preceding claim, wherein the sample additionally comprises non-motile spermatozoa and spermatozoa with reduced motility.
 - 6. An apparatus according to any preceding claim, comprising a spermatozoa detection means on the outlet side of the sample separation filter, and spaced therefrom.
- 7. An apparatus according to claim 6, wherein the detection means is integral with the 20 apparatus.
 - 8. An apparatus according to claim 6, wherein the detection means is a separable component of the apparatus for inserting into the apparatus before, during or after placing the sample separation filter in contact with the liquid medium.
- An apparatus according to any preceding claim, wherein the filter has a thickness of
 100-2000µm.
 - 10. An apparatus according to claim 9, wherein the filter has a thickness of $200\text{-}1000\mu\text{m}$, preferably $400\text{-}800\mu\text{m}$.
 - 11. An apparatus according to claim 10, wherein the filter has a thickness off about 600µm.

WO 00/09648 PCT/GB99/02685

-14-

- 12. An apparatus according to any preceding claim, wherein the filter has a minimum particle retention size of 5-100μm, preferably 8-60μm, more preferably 10-40μm.
- 13. An apparatus according to any preceding claim, wherein the filter has an underlying grid lattice for supporting the filter.
- 5 14. An apparatus according to any of claims 6 to 13, wherein a reagent or a combination of reagents which is/are directly or indirectly capable of generating a visual signal on interaction with spermatozoa is/are located in the spermatozoa detection means.
 - 15. An apparatus according to claim 14, wherein the reagent or combination of reagents include antibodies that detect an antigen present on spermatozoa and are capable of binding spermatozoa.
 - 16. An apparatus according to claim 15, wherein spermatozoa, when immobilised by the antibodies, can be visually detected using a visually detectable reagent which binds to spermatozoa.
- 17. An apparatus according to any of claims 6 to 16, wherein a spermatozoa chemoattractant is located in the spermatozoa detection means.
 - 18. An apparatus according to claim 17, wherein the spermatozoa chemoattractant is located in a portion of the spermatozoa detection means distal from the sample separation filter.
- 19. An apparatus according to any of claims 6 to 18, wherein a pick-up zone is located either in the sample separation filter or the spermatozoa detection means, said pick-up zone comprising a reagent or combination of reagents which is/are capable of binding to spermatozoa and being transported therewith to a detection area of the spermatozoa detection means.
 - 20. An apparatus according to claim 19, wherein the reagent or combination of reagents of the pick-up zone include antibodies that detect an antigen present on spermatozoa.
- 25 21. An apparatus according to claim 20, wherein the antibodies that detect an antigen present on spermatozoa are detectably labelled.
 - 22. An apparatus according to claim 21, wherein the antibodies that detect an antigen present on spermatozoa are detectably labelled with gold particles.

WO 00/09648


25


- 23. An apparatus according to claim 20, claim 21 or claim 22, wherein the antibodies that are located in a detection area of the spermatozoa detection means recognise a different spermatozoa antigen compared to the antibodies located in the pick-up zone.
- 24. An apparatus according to claim 20, claim 21 or claim 22, wherein the antibodies that are located in a detection area of the spermatozoa detection means recognise the same spermatozoa antigen as the antibodies located in the pick-up zone.
 - 25. An apparatus according to any of claims 6 to 24, wherein the spermatozoa detection means comprises a spermatozoa acrosome-lysing reagent and a means for detecting pH change.
- 26. An apparatus according to claim 25, wherein the spermatozoa acrosome-lysing reagent10 is a lysis buffer.
 - 27. An apparatus according to claim 26, wherein the lysis buffer comprises Proteinase K or the calcium ionophore A24297.
 - 28. An apparatus according to claim 25, claim 26 or claim 27, wherein the means for detecting pH change is a pH sensitive probe.
- 15 29. An apparatus according to claim 25, claim 26 or claim 27, wherein the means for detecting pH change is a pH indicator reagent capable of visually detecting a pH change.
 - 30. An apparatus according to claim 29, wherein the pH indicator reagent is bromocresol purple.
- 31. An apparatus according to any of the preceding claims, wherein the sample receiving surface of the sample separating filter contains an enzymatic liquefaction agent.
 - 32. A male fertility testing kit comprising an apparatus according to any one of claims 6 to 31, the kit comprising a liquid release mechanism, wherein upon activation of the liquid release mechanism, liquid from a liquid supply is applied to the sample filtered end of the sample separation filter to provide liquid communication with the spermatozoa detection means.
 - 33. A kit according to claim 32, wherein the detection means is a separable component of the kit.
 - 34. The kit of claim 32 or claim 33, comprising an integral liquid supply.

25


- 35. The kit of claim 34, wherein liquid contained within the liquid supply is a buffer.
- 36. The kit of any one of claims 32 to 35, wherein the apparatus and a base unit form two separable components of the kit.
- 37. The kit of claim 36, wherein application of the apparatus to the base unit causes activation of the liquid release mechanism.
 - 38. The kit of any one of claims 32 to 36, wherein a button release is provided for activating the liquid release mechanism.
 - 39. The kit according to any of claims 32 to 38, wherein wetting the spermatozoa detection means with the liquid activates detecting agents applied thereto.
- 10 40. The kit according to any of claims 32 to 39, further comprising an overflow container for containing any excess liquid applied to the apparatus upon activation of the liquid release mechanism.
 - 41. The kit according to any of claims 32 to 40 incorporating the liquid supply, the liquid supply comprising a frangible compartment, wherein the liquid release mechanism breaks the compartment to release liquid contained therein.
 - 42. The kit according to claim 41, wherein liquid released from the compartment is channelled by a ramp towards a well formed between the apparatus and a base portion of the kit.
 - 43. The kit according to claim 41 or claim 42, wherein the compartment is piercable and the liquid release mechanism is a piercing mechanism.
- 20 44. The kit according claim 43, wherein the piercing mechanism is retained by a stop, the stop preventing the piercing mechanism from piercing the compartment until activated by a user.
 - 45. A method of detecting the presence of motile sperm in a sample, comprising:
 - (a) providing a filter having first and second surfaces, the filter permitting migration of the motile sperm therethrough when a liquid is applied to the second surface,
 - (b) applying the sample to the first surface,
 - (c) applying a liquid to the second surface, and
 - (d) detecting sperm that has migrated through the filter.

- 46. The method of claim 45, wherein the filter is the filter contained within the apparatus of any of claims 1 to 31.
- 47. The method of claim 43, wherein the filter is the filter contained within the kit of any of claims 32 to 44.
- 5 48. An apparatus for separating motile spermatozoa from non-motile spermatozoa substantially as hereinbefore described with reference to the accompanying drawings.
 - 49. A male fertility testing kit substantially as hereinbefore described with reference to the accompanying drawings.
- 50. A method for detecting an analyte in a sample substantially as hereinbefore described with reference to the accompanying drawings.
 - 51. A method of detecting motile spermatozoa in a sample substantially as hereinbefore described with reference to the accompanying drawings.





2/2



DOCKET NO.: <u>49447-2USPX</u>

COMBINED DECLARATION AND POWER OF ATTORNEY

I hereby classified below: Application No. I hereby classified and PCT is matter of each of the International application disclose to the O	International application designed claims of this application is eation in the manner provided affice all information known to choccurred between the filing application: I No. Filing	C. § 120 of any United States appropriate the United States listed by not disclosed in the prior United by the first paragraph of 35 U.S. of the to be material to patentability date of the prior application and the Date States of the States of the States of the Prior application and the Date States of the Sta	elow and, insofar as the subject
I hereby classified below: Application No. I hereby classified as a second se	laim the benefit under 35 U.S. International application design to claims of this application is eation in the manner provided all information known to choocurred between the filing	.C. § 120 of any United States appropriating the United States listed by not disclosed in the prior United by the first paragraph of 35 U.S. one to be material to patentability.	plication(s) listed below, or § elow and, insofar as the subject States application or PCT C. § 112, I acknowledge the duty by of the application as defined in
I hereby classed below:	Month/Day/Y	Year Filed Status (Per	nding, abandoned, patented)
I hereby cl			
UD	aim the benefit under 35 U.S.	C. § 119(e)(1)-(2) of any United	States provisional application(s)
GB	9817795.9	August 14, 1998	
Country	Number	Date Filed	Priority <u>Claimed</u>
I hereby cla application(s) for pa designated at least o application(s) for pa	application as defined in 37 C aim foreign priority benefits u atent or inventor's certificate(s	ander 35 U.S.C. § 119(a)-(d) or § a), or § 365(a) of any PCT International States, listed below and have	365(b) of any foreign
	, as amended by any amendm	•	me to be material to the
I hereby sta	ite that I have reviewed and u	nderstand the contents of the above	ve identified specification,
is att Xwa	tached hereto. Is filed on as Appli	ication Serial No	
original first and ini	int inventor (if plural names and any in the invention entitled:	st and sole inventor (if only one n re listed below) of the subject ma SEPARATION AND DETEC	itter which is claimed and for
	ce, post office address and citi	izenship are as stated below next	to my name; and
·			
My residence	named inventor, I hereby dec	lare that:	

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: BENJAMIN J. BAI, Reg. No. 43,481; TIMOTHY G. ACKERMANN, Reg. No. 44,493; THOMAS L. CRISMAN, Reg. No. 24,846; THOMAS L. CANTRELL, Reg. No. 20,849; STUART D. DWORK, Reg. No. 31,103; WILLIAM F. ESSER, Reg. No. 38,053; J. KEVIN GRAY, Reg. No. 37,141; STEVEN R. GREENFIELD, Reg. No. 38,16; ROGER L. MAXWELL, Reg. No. 31,855; LISA H. MEYERHOFF, Reg. No. 36,869; STANLEY R. MOORE, Reg. No. 26,958; P. WESTON MUSSELMAN, JR., Reg. No. 31,644; SPENCER C. PATTERSON, Reg. No. 43,849; ANDRE M. SZUWALSKI, Reg. No. 35,701; RICHARD J. MOURA, Reg. No. 34,883, ROBERT WILLIAM MASON, Reg. No. 42,848; JAMES F. LEA, Reg. No. 41,143, RUSSELL N. RIPPAMONTI, Reg. No. 39,521; KEITH W. SAUNDERS, Reg. No. 41,462; JERRY R. SELINGER, Reg. No. 26,582; TAMSEN VALOIR, Reg. No. 41,417; RAYMOND VAN DYKE, Reg. No. 34,746 and GERALD T. WELCH, Reg. No. 30,332 of the firm of JENKENS & GILCHRIST, P.C., 3200 Fountain Place, 1445 Ross Avenue, Dallas, Texas 75202-2799; and

Address all telephone calls and correspondence to: P. Weston Musselman, Jr., Esq. Jenkens & Gilchrist, P.C. 3200 Fountain Place, 1445 Ross Avenue Dallas, Texas 75202-2799 Telephone: 214-855-4764, Facsimile: 214-855-4300

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

1	Paul BATEMAN Full Name	Inventor's Signature	Date
_	12-50 Kingsgate Road, Kingston-U	Jpon-Thames	GB
	KT2 5AA, Great Britain Residence		Citizenship
	same as above Post Office Address		
2	Full Name	Inventor's Signature	Date
	Residence		Citizenship
	Post Office Address		

United States Patent & Trademark Office

Office of Initial Patent Examination -- Scanning Division



Application deficient	sies were it	build during scaining.	
☐ Page(s)for scanning.	of	abstract (Document title)	were not present
☐ Page(s)for scanning.	of	(Document title)	were not present
□ Scanned copy	is best avai	lable.	